

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/086545 A2

(51) International Patent Classification⁷:

H01M 8/04

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/JP2004/002444

(22) International Filing Date: 27 February 2004 (27.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-089089 27 March 2003 (27.03.2003) JP

(71) Applicant (for all designated States except US): NISSAN MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama-shi Kanagawa, 2210023 (JP).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and

Published:


(75) Inventor/Applicant (for US only): SAKAI, Hiromasa [JP/JP].

— without international search report and to be republished upon receipt of that report

(74) Agents: MIYOSHI, Hidekazu et al.; 9th Floor, Toranomon Daiichi Building, 2-3, Toranomon 1-chome, Minato-ku Tokyo, 1050001 (JP).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTROL DEVICE OF VEHICULAR FUEL CELL SYSTEM AND RELATED METHOD



WO 2004/086545 A2

(57) Abstract: A control device (10) for a vehicular fuel cell system (S) is provided with a warm-up output control section (8) operative, when a fuel cell system is started up under a low temperature condition and in case that a fuel cell stack of the fuel cell system is warmed up, causing the fuel cell stack to generate electric power to allow predetermined warm-up electric power to be taken out, and a run permission section (7) operative, during a period wherein the warm-up electric power is taken out by the warm-up output control section, to discriminate whether the fuel cell stack assumes a predetermined warm-up condition on the basis of one of a voltage value and an electric current value of the fuel cell stack. And, when discrimination is made that the fuel cell stack assumes the predetermined warm-up condition, the run permission section provides a vehicle with run permission.